

### FOTON AUMAN ETX 10W TRACTOR HEAD



<b>Basic Information</b>	Function	Tractor
	Drive Style	6x4
	Platform	ETX
	Vehicle Model	BJ4253SMFKB-01
	Inner Model	4253SMFKB-01ZA09
<b>Dimensions</b>	Wheelbase (mm)	3300+1350
	Overall (LxWxH) mm	6910x2495x3460
	Chassis (LxWxH) mm	/
	Cargo (LxWxH) mm	/
<b>Weight</b>	Chassis Curb Weight (kg)	9500
	Rated Payload (kg)	/
	GVW/GCW (kg)	55000 / 8,000
<b>Performance</b>	Maximum Speed (km/h)	92(4.8) / 98(4.38) / 76(5.73)
	Maximum Climbing Capacity, % (full load)	29(4.8) / 26(4.38) / 35(5.73)
<b>Cab</b>	Body Type	ETX-2490 High Roof
	Carrying Number	2, Double Bed
<b>Engine</b>	Engine Model	WD618.42Q
	Engine Type	In-line, Six-cylinder, Water Cooling, Four-stroke, DI, Turbocharging, Intercooling, Diesel Engine
	Displacement (L)	11.596
	Rated Power	309 kw, 420 PS, 2200 rpm
	Max Torque	1600 N.m @ 1300-1600 rpm
<b>Clutch</b>	Plate Diameter	φ430
<b>Gearbox</b>	Gearbox Model	12JSD180TA with Synchronizer
	Gear	12 Forward + 2 Reverse
	Gearbox Brand	FAST
<b>Brake</b>	Service Brake	Dual Circuits Pneumatic Brake
	Parking Brake	Energy-accumulating spring air cut-off brake
	Auxiliary Brake	Engine Exhaust Valve and Exhaust Butterfly Brake
<b>Suspension</b>	Front Suspension	Spring Suspension, 9 Pieces
	Rear Suspension	Spring Suspension, 12 Pieces
<b>Front Axle</b>	Rated Load	7.5T
	Brake Type	Drum Brakes
<b>Rear Axle</b>	Type / Main Reduction Ratio	STR 16T Hub Reduction Rear Axle / 4.8
	Differential Lock	Axle and Wheel Differential Lock
	Brake Type	Drum Brakes
<b>Tyre</b>	Tyre Model	11R22.5
	Total Quantity	10+1
<b>Steering Gear</b>	Steering Gear Model	AM90H-S
<b>Fuel Tank</b>	Fuel tank Cubage	350L AI
<b>Electrical System</b>	Rated Voltage	24V
<b>Basic Equipment</b>		Air Bag Seat, Manual Cabin Lifting, Manual Rear-view Mirror and Glass Lifter
<b>Other</b>		Air Conditioner, Air Deflector, 50# Fifth Wheel
<b>Tire Options</b>		315/80R22.5, 12.00R20

