

FOTON AUMAN GTL 10W TRACTOR HEAD



Basic Information	Function	Tractor
	Drive Style	6x4
	Platform	GTL
	Vehicle Model	BJ4259SMFKB-26
	Inner Model	4259SMFKB-26ZA01
Dimensions	Wheelbase (mm)	3300+1350
	Overall (LxWxH) mm	6940×2490×3890
	Chassis (LxWxH) mm	/
	Cargo (LxWxH) mm	/
Weight	Chassis Curb Weight (kg)	9800
	Rated Payload (kg)	/
	GVW/GCW (kg)	90000 / 8000
Performance	Maximum Speed (km/h)	100
	Maximum Climbing Capacity, % (full load)	≥20
Cab	Body Type	GTL-2490 High Roof
	Carrying Number	2, Double Bed
Engine	Engine Model	ISGe3-430
	Engine Type	In-line, Six-cylinder, Water Cooling, Four-stroke, DI, Turbocharging, Intercooling, Diesel Engine
	Displacement (L)	11.8
	Rated Power	315 kw, 430 PS, 1900 rpm
	Max Torque	2000/1000
Clutch	Plate Diameter	Φ430
Gearbox	Gearbox Model	12JSD180TA with Synchronizer
	Gear	12 Forward + 2 Reverse
	Gearbox Brand	FAST
Brake	Service Brake	Dual circuit Pneumatic Brake
	Parking Brake	Energy-accumulating Spring Air Cut-off Brake
	Auxiliary Brake	Cummins Engine Brake
Suspension	Front Suspension	Spring Suspension, 9 Pieces
	Rear Suspension	Spring Suspension, 12 Pieces
Front Axle	Rated Load	7.5T
	Brake Type	Drum Brakes
Rear Axle	Type / Main Reduction Ratio	Benz 16T Hub Reduction Rear Axle / 4.76 with ABS
	Differential Lock	Axle and Wheel Differential Lock
	Brake Type	Drum Brakes
Tire	Tire Model	12.00R20
	Total Quantity	10+1
Steering Gear	Steering Gear Model	ZF8098
Fuel Tank	Fuel tank Cubage	700L AI
Electrical System	Rated Voltage	24V
Basic Equipment		Desert Air Filter, Air Bag Seat, Full-floating Tiltable Cabin, Electric Rear-view Mirror and Power Window
Other		Air Conditioner, Air Deflector, 50# Fifth Wheel
Tire Options		315/80R22.5

