

FAW STARK 4x2 MINI DUMP TRUCK 5CBM



| | | |
|---------------------|------------------------|---|
| Model | | CA3075P40K2EA84 |
| Platform | | STARK |
| Cabin | | Cabin, Radio with USB, 2 Speakers, Manual Aircon, Electric Doors and Windows / Central Lock |
| Weight | Curb Weight | 3,030 kg |
| | Payload (kg) | 8,000 kg |
| | Actual GVW (kg) | 11,030 kg / 4,200 kg |
| Dimensions | Overall Dimension (mm) | 5450 x 2100 x 2405 |
| | Body Size (mm) | 3600x2100x650, 5 CBM, Middle Lift, Hydraulic Bottom: 5mm, Side: 4mm |
| | Wheelbase | 3300 mm |
| Performance | Max. Speed | 90 km/h |
| Engine | Brand | YUCHAI |
| | Model | YC4D130-33 |
| | Type | EGR |
| | Power | 130 HP |
| | Displacement | 4.2 L |
| | Max. torque | 420 N.m / 1400~1800 rpm |
| Transmission | Brand | WLY |
| | Model | 6TS55 |
| | Gear Shift | Manual 6 Speed |
| | Ratio | i1: 6.158, i2: 3.826, i3: 3.361, i4: 2.224, i5: 1, i6: 0.768, Reverse: 5.708 |
| Clutch | Brand | - |
| | Diameter | Φ330 |
| Brakes | Type | Full Air Brake System, Split Pneumatic Circuit |
| | Park brake | Air-cut Brake |
| | Auxiliary brake | Exhaust Brake |
| Chassis | Type | Side Rails, Punched and Riveted Construction, 216*75*6 |
| Suspension | Front Suspension | Front 7 Parabolic |
| | Rear Suspension | Rear 10+3 Spring |
| Axles | Front axle | X141B 3 Tons |
| | Rear axle | Qingte 1080/ 8T |
| | Ratio | 5.286 |
| Tires | Model | 8.25R16 14PR |
| Fuel Tank | Tank Capacity | 100L, Steel Tank |

