

拖泵
Trailer Pump

SHANTUI
VALUE THAT WORKS



隧道王
TUNNEL KING

SHANTUI - Janeeo
VALUE THAT WORKS

拖泵系列
Trailer Pump Series



拖泵
Trailer Pump

细石混凝土泵 (电机) Fine Aggregate Concrete Trailer Pump (motor)



泵送系统	型号 Model	SHBT1506SD	SHBT2006SD	SHBT2506SD
理论最大输送量 Maximum Theoretical Conveying Capacity (m ³ /h)		15	20	25
理论最大输出压力 Maximum Theoretical Output Pressure (Mpa)		7	8	8
混凝土分配阀 Concrete Distribution Valve		S管阀 (pipe valve)	S管阀 (pipe valve)	S管阀 (pipe valve)
混凝土坍落度范围 Concrete Slump Range (mm)		180~220	180~220	180~220
输送缸缸径×行程 Conveyor Cylinder Bore×Stroke (mm)		φ140×575	φ140×700	φ140×700
主油缸缸径×行程 Master Cylinder Bore×Stroke (mm)		φ80×φ55×575	φ80×φ55×700	φ80×φ55×700
料斗容积/上料高度 Hopper Capacity/Loading Height (L/mm)		300/1100	300/1100	300/1100
最大骨料粒径 Maximum Aggregate size (mm)		30	30	30
功率/转速 Power/Speed (kW/min)		22/1480	30/1480	37/1480
总质量 Gross weight (kg)		1950	2200	2500
外形尺寸(长×宽×高) Overall Dimensions(L×W×H) (mm)		3900×1350×1450	4200×1530×1650	4500×1510×1890

注: 以上参数有可能变动, 以产品为准! All specification is subject to modification!

泵送系统	型号 Model	SHBT3010SD	SHBT4010SD	SHBT4510SD
理论最大输送量 Maximum Theoretical Conveying Capacity (m ³ /h)		30	40	45
理论最大输出压力 Maximum Theoretical Output Pressure (Mpa)		10	10	13
混凝土分配阀 Concrete Distribution Valve		S管阀 (pipe valve)	S管阀 (pipe valve)	S管阀 (pipe valve)
混凝土坍落度范围 Concrete Slump Range (mm)		180~220	180~220	180~220
输送缸缸径×行程 Conveyor Cylinder Bore×Stroke (mm)		φ100×1000	φ160×1000	φ180×1000
主油缸缸径×行程 Master Cylinder Bore×Stroke (mm)		φ100×φ63×1000	φ100×φ63×1000	φ110×φ70×1000
料斗容积/上料高度 Hopper Capacity/Loading Height (L/mm)		400/1100	400/1100	400/1100
最大骨料粒径 Maximum Aggregate size (mm)		30	30	30
功率/转速 Power/Speed (kW/min)		45/1480	55/1480	55/1480
总质量 Gross weight (kg)		3000	3200	3200
外形尺寸(长×宽×高) Overall Dimensions(L×W×H) (mm)		4750×1600×1990	4820×1600×1950	4570×1980×2090

注: 以上参数有可能变动, 以产品为准! All specification is subject to modification!

5 专业的混凝土设备

SHANTUI - Jareco | 拖泵



混凝土泵 (电机)
Concrete Trailer Pump (motor)

泵送系统	型号 Model	SHBT5013SD	SHBT6012SD	SHBT8016SD
理论最大输送量 Maximum Theoretical Conveying Capacity (m ³ /h)		50	60 (45/69)	50/65
理论最大输出压力 Maximum Theoretical Output Pressure (Mpa)		13	12(13)	16
混凝土分配阀 Concrete Distribution Valve		S管阀 (pipe valve)	S管阀 (pipe valve)	S管阀 (pipe valve)
混凝土坍落度范围 Concrete Slump Range (mm)		180~220	180~220	180~220
输送缸缸径×行程 Conveyor Cylinder Bore×Stroke (mm)		φ200×1050	φ200×1650	φ200×1800
主油缸缸径×行程 Master Cylinder Bore×Stroke (mm)		φ125×φ80×1050	φ125×φ80×1650	φ140×φ90×1800
料斗容积/上料高度 Hopper Capacity/Loading Height (L/mm)		500/1400	500/1400	500/1400
最大骨料粒径 Maximum Aggregate size (mm)		40	φ45(φ40) / φ50(φ45) / 50	φ45(φ40) / φ50(φ45) / 50
功率/转速 Power/Speed (kW/min)		75/1480	90/1480	110/1480
总质量 Gross weight (kg)		4200	5600	6200
外形尺寸(长×宽×高) Overall Dimensions(L×W×H) (mm)		4590×1980×2100	6490×1980×2300	7125×1980×2300

注: 以上参数有可能变动, 以产品为准! All specification is subject to modification!



8S砂浆泵王
8S Mortar Pump

泵送系统	型号 Model	SHBT8016SD
理论最大输送量 Maximum Theoretical Conveying Capacity (m ³ /h)		8
理论最大输出压力 Maximum Theoretical Output Pressure (Mpa)		8
混凝土分配阀 Concrete Distribution Valve		S管阀 (pipe valve)
混凝土坍落度范围 Concrete Slump Range (mm)		150~220
输送缸缸径×行程 Conveyor Cylinder Bore×Stroke (mm)		φ140×1000
主油缸缸径×行程 Master Cylinder Bore×Stroke (mm)		φ80×φ55×1000
料斗容积/上料高度 Hopper Capacity/Loading Height (L/mm)		400/1080
最大骨料粒径 Maximum Aggregate size (mm)		卵石(φ)≤10, 卵石(φ)≤15
功率/转速 Power/Speed (kW/min)		37/1480
总质量 Gross weight (kg)		2800
外形尺寸(长×宽×高) Overall Dimensions(L×W×H) (mm)		4450×1570×1830

注: 以上参数有可能变动, 以产品为准! All specification is subject to modification!

6 Professional concrete equipment

